

**SPI-335-34**

Ultraminiature photoreflector (single-transistor type)

Features

- Infrared LED plus Phototransistor (single)
- DIP type
- Compact type : 3.4 (L) × 2.7 (W) × 1.5 (H) mm
- Visible light cut type
- Lead length : (L=3.5mm)

Absolute Maximum Ratings at Ta=25°C, 65%RH

| Parameter | | Symbol | Rating | Unit |
|--------------------------|---------------------------|------------------|-------------|------|
| Input LED | Forward Current | I _F | 50 | mA |
| | Reverse Voltage | V _R | 5 | V |
| | Power Dissipation | P _D | 70 | mW |
| Output Phototransistor | Collector-Emitter Voltage | V _{CEO} | 20 | V |
| | Emitter-Collector Voltage | V _{ECO} | 5 | V |
| | Collector Current | I _C | 20 | mA |
| | Power Dissipation | P _C | 70 | mW |
| Operating Temperature | | T _{opr} | -20 to +80 | °C |
| Storage Temperature | | T _{stg} | -40 to +100 | °C |
| Soldering Temperature *1 | | T _{sol} | 260 | °C |

*1 Soldering conditions : time : max. 3sec; clearance : min. 1mm from lower case edge.

Electro-Optical Characteristics at Ta=25°C, 65%RH

| Parameter | | Symbol | Condition | Min. | Typ. | Max. | Unit |
|-----------|--------------------------------------|----------------------|---|------|------|------|------|
| Input | Forward Voltage | V _F | I _F =10mA | 1.0 | 1.2 | 1.6 | V |
| | Reverse Current | I _R | V _R =5V | - | - | 10 | μA |
| Output | Dark Current | I _{CEO} | I _F =0mA, V _{CE} =10V | - | 10 | 200 | nA |
| Coupled | Collector Output Current | I _C | I _F =4mA, V _{CE} =5V*1 | 33 | - | 180 | μA |
| | Leakage Current | I _{LEAK} | I _F =10mA, V _{CE} =5V*2 | - | - | 1 | μA |
| | Collector Emitter Saturation Voltage | V _{CE(sat)} | I _F =10mA, I _C =50μA | - | - | 0.5 | V |
| | Rise Time | t _r | V _{CC} =5V, R _L =100Ω | - | 5 | - | μs |
| | Fall Time | t _f | I _C =1mA | - | 5 | - | μs |

*1 Location of reflector is show in Fig. 1.

*2 No reflector

*3 Table of Classification of Collector Output

| Class | E | F | G | H |
|---------------------|------------|-----------|-----------|----------|
| I _c (μA) | 180 to 110 | 140 to 80 | 100 to 50 | 65 to 33 |
| Marking color | Orange | Green | White | Silver |




Fig. 1 Location of Reflector

Package dimensions and Pin connection

As stated in the sttached paper. (No.6029 5/6)

Rank marking of collector output

The bottom of the package is colored following the table of classification of collector output.

Lot marking

Color division shall be done as shown in the drawing. (Fig. 2)

Year of even number : Front side

Year of odd number : Back side




Fig. 2

| Color | Black | Blue | Red | Green | Orange | Brown |
|----------|---------|----------|-----------|---------|----------|----------|
| Part 'A' | January | February | March | April | May | June |
| Part 'B' | July | August | September | October | November | December |

Soldering conditions

- (1) Temperature : Max. 260°C
- (2) Time : Max. 3sec
- (3) Clearance : Min. 1mm from the case edge. (Fig. 3)





Fig. 3




⚠ PRECAUTIONS

- (1) Bending a lead should avoid. However, when bending is necessary, take care the next items.
 - ① Bending a lead must be done before soldering.
 - ② Bending a lead must be done in the states of fixing leads and no stress for the regin part. Because it is possible that stress for the regin part cause troubles such as gold wire breaking and so on.
 - ③ A lead must be bend at intervals of 2mm from the case edge.
 - ④ Do not bend the same position of leads more than twice.
- (2) The hole pitch of a circuit board must fit to the lead pitch.
- (3) Take core the following when soldering.
 - ① Do not heat a product under any stress (a twist and so on) to leads.
 - ② Do not heat a product in the states of operating force to the regin part.
- (4) Use the flux which contain no chlorine, have no corrosion and do not need washing.
- (5) Be careful that flux or other chemicals do not attach to the luminous surface and passive surface.

SPI-335-34



Pin Connection
 1. Ph. Tr Emitter
 2. Ph. Tr Collector
 3. LED Cathode
 4. LED Anode



* M : Color marking of Ic class


Tolerance : ± 0.2
 Unit : mm

Typical Characteristics




These numerical value show the electrical and optical characteristics of this product, and not assure this contents.


Forward Current vs. Ambient Temperature (Rating)




Power Dissipation vs. Ambient Temperature (Rating)




Forward Current vs. Forward Voltage




Collector vs. Forward Current



Collector Current vs. Collector-emitter Voltage






Relative Collector Current vs. Ambient Temperature






Typical Characteristics



These numerical value show the electrical and optical characteristics of this product, and not assure this contents.



Test Circuit for Response Time



 **CAUTION**

1. No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster / crime-prevention equipment or the like, and the failure of which may directly or indirectly cause injury, death or property loss.
2. Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - 1) Accept full responsibility and indemnify and defend SANYO ELECTRIC CO.,LTD., it's affiliates, subsidiaries and distributors or any of their officers and employees, jointly and severally, against any and all claims and litigation and all damages, costs and expenses associated with such use.
 - 2) Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., it's affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
3. Information (including circuit diagrams and circuit parameters) disclosed herein is for example only; it is not guaranteed for mass production, SANYO believes the information disclosed herein is accurate and reliable, but no guarantees are made or implied regarding it's use or any infringements of intellectual property rights or other rights of third parties.

Precautionary instructions in handling gallium arsenic products

Special precautions must be taken in handling this product because it contains, gallium arsenic, which is designated as a toxic substance by law. Be sure to adhere strictly to all applicable laws and regulations enacted for this substance, particularly when it comes to disposal.

Manufactured by ; **Tottori SANYO Electric Co., Ltd.**
LED Division
5-318, Tachikawa-cho, Tottori City, 680-8634 Japan
TEL: +81-857-21-2137 FAX: +81-857-21-2161